

LED Slim Lightbox Instruction and Notification

1. LES Wide Viewing Angle Slim Lightbox



Step1. Open the magnetic frame.



Step2. Insert the translucent graphics into the left side, and then right side.



Step3. Smooth the graphics and then insert into the bottom.



Step4. Close the magnetic frame.

2. LNS Unilateral Open Slim Lightbox



Step1. Remove the magnetic frame temporarily.



Step2. Insert the translucent graphics into the left side, and then right side.



Step3. Smooth the graphics and then insert into the bottom.



Step4. Put the magnetic frame back.

3. LCS Frameless Slim Lightbox



Step1. Draw out the acrylic cover, and remove the protect film on the cover.



Step2. Remove the protect film on the lightbox.



Step3. Smooth the graphics and then insert into the bottom.



Step4. Put the acrylic cover back.

4. LDS Dual-side Sleek Slim Lightbox

Basic



Step1. Remove the protect film on the lightbox.



Step2. Remove the screws of the short side without the DC terminal.



Step3. Draw out the aluminium component.



Step4. Insert the translucent graphics, put the component back, and tighten the screws.

5. LRS Side Plug-in Slim Lightbox



Step1. Open the magnetic frame.



Step2. Insert the translucent graphics into both sides.



Step3. Smooth the graphics and then insert into the bottom.



Step4. Close the magnetic frame.



Step1. Open the magnetic front cover.



Step2. Put the translucent graphics on the lightbox, and put the cover back.

Advanced

※ LED Slim Lightbox Notification ※

1. Use the compatible transformer to drive the lightbox (12V/DC input).
2. Suitable for internal application without waterproof.
3. Please check the integrity of the wire before installation.
4. Do not connect the lightbox with other electric products at the same time.